

LEVELLING AND CUT TO LENGTH LINE

SECOND HAND

FIMI

2.000 x 2,0 ÷ 6,0 mm.



SHL - Levelling and Cut to Length Line 2.000 x 2,0 ÷ 6,0 mm.

MATERIAL SPECIFICATIONS

Inlet material			
Material	Carbon Steel		
Tensile Strength	Max	600	N/mm ²
Yield Strength	Max	400	N/mm ²
Elongation	Max	20	%
Strip Thickness	Min.	1,5	mm
	Max	6,0	mm
Strip Width	Min.	500	mm
	Max	2.050	mm
Coil data			
Weight	Max	30	Ton.
Inside Diameter	610-760-850		mm
Outside Diameter	Max	2.000	mm
Outlet material			
Sheet Data			
Length	Min.	1.000	mm
	Max	8.000	mm
Width	Min.	800	mm
	Max	2.100	mm
Sheet	Min.	500	mm
	Max	6.000	mm
Tolerance	+/-	0,5	mm
Weight	Max	6.000	Kg.
Stacking Method			
Stacking	Into pallet or without pallet		

SHL - Levelling and Cut to Length Line 2.000 x 2,0 ÷ 6,0 mm.

CHARACTERISTICS OF THE LINE

Manufacturing Year	1991		
Inlet speed	Max	5	m/min.
Working speed	Max	50	m/min.
Line Direction	Right to Left		
Line Reference	Centre		
Pass Line Height	1.500	mm	

SHL - Levelling and Cut to Length Line 2.000 x 2,0 ÷ 6,0 mm.

