

NARROW SLITTING LINE

SECOND HAND

GUIDA

750 x 3,0 ÷ 14,0 mm.



SHL - Levelling and Cut to Length Line 2.000 x 2,0 ÷ 6,0 mm.

MATERIAL SPECIFICATIONS

Inlet material			
Material	Galvanized,HRC-CRC-Stainless Steel		
Tensile Strength	Max	800	N/mm ²
Yield Strength	Max	520	N/mm ²
Strip Thickness	Min.	3,0	mm
	Max	14,0	mm
Strip Width	Min.	150	mm
	Max	755	mm
Coil data			
Weight	Max	12,5	Ton.
Inside Diameter		600 ÷ 700	mm
Outside Diameter	Min.	914	mm
	Max	2040	mm
Outlet material			
Coil Data			
Weight	Max	12,5	Ton
Internal Diameter		610	mm
External Diameter	Min	800	mm
	Max	2000	mm
Width	Min	150	mm
	Max	750	mm

SHL - Levelling and Cut to Length Line 2.000 x 2,0 ÷ 6,0 mm.

CHARACTERISTICS OF THE LINE

Working speed	Max	25	m/min.
Working Direction	Left to Right		
Line Reference	Center		
Pass Line Height	1.200	mm	
Uncoiling	From the top		
Recoiling	From the top		
Working Conditions	Min.	+ 5	°C
	Max.	+ 40	°C

Circular Blades Shear

DC Motor	145	kW
Shaft Diameter	350	mm
Blades Diameter	550	mm
Cutting Heads Available	2	

SHL - Levelling and Cut to Length Line 2.000 x 2,0 ÷ 6,0 mm.

